

Application Serial No. 09/994,283
Reply to Office Action of December 12, 2006

PATENT
Docket No. CU-2732

Amendments To The Claims

The listing of claims presented below will replace all prior versions, and listings, of claims in the application.

Listing of claims:

1. (Currently amended) A liquid crystal display device having upper and lower substrates and an active area having pixels for display displaying an image, the display device comprising:

a supporting column extending from the upper substrate to a the lower substrate so as to maintain a uniform cell gap therebetween, said supporting column having an outer surface inclined relative to, ~~with respect to~~ the lower substrate at a first angle, relative to the lower substrate;

a contact part having an interior surface that is inclined with respect to the lower substrate at a second angle, relative to the lower substrate, the second angle being that is different than the first angle, said contact part being provided for a common line disposed at a peripheral region outside the active area of the lower substrate opposite to the upper substrate, wherein the contact part faces the supporting column at a corresponding position so as to guide electrical communication between the supporting column and the common line; and

an electrically conductive layer formed on the outer surfaces of the supporting column and on a corresponding outer surface of the upper substrate, wherein a portion of the electrically conductive layer on the supporting column is joined to the common line within the contact part so as to establish a signal interconnection between the lower

Application Serial No. 09/994,283
Reply to Office Action of December 12, 2006

PATENT
Docket No. CU-2732

substrate and the upper substrate.

2. (original) The liquid crystal display device of claim 1, wherein an insulating layer is further provided for the common line, and the contact part is a contact hole formed in the insulating layer so as to expose a portion of the common line.

3. (Currently amended) A method for fabricating a liquid crystal display device upper and lower substrates and having an active area having pixels for displaying an image, the method display, comprising the steps of:

providing a supporting column extending from the upper substrate to a lower substrate so as to maintain a uniform cell gap between ~~the outer surface of the upper~~ substrate and the lower substrate, said supporting column having an outer surface inclined with respect to the lower substrate to form a first angle between the outer surface of the supporting column and the lower substrate; ~~at a first angle;~~

forming an electrically conductive layer on the outer surface of the supporting column and on the upper substrate;

providing a contact part for a common line disposed at a peripheral region outside the active area of the lower substrate confronting the upper substrate, wherein the contact part faces the supporting column at a corresponding position and having an interior surface that is inclined with respect to the lower substrate to form a second angle between said interior surface and the lower substrate, said second angle being at ~~a second angle that is different than the first angle;~~ and

uniting the lower substrate and the upper substrate so that a portion of the electrically conductive layer on the supporting column is joined to the common line within the contact part, thereby establishing a signal interconnection between the lower

Application Serial No. 09/994,283
Reply to Office Action of December 12, 2006

PATENT
Docket No. CU-2732

substrate and the upper substrate.

4. (original) The method of claim 3, wherein the providing of the contact part includes providing an insulating layer for the common line and forming a contact hole in the insulating layer so as to expose a portion of the common line.

5. (original) The method of claim 3, wherein the electrically conductive layer includes an indium tin oxide (ITO) layer.

6. (Cancelled)